

PRODUCT DATA SHEET



TOPKLEAN EL 7

Solvent for Stencil Cleaning in Printers

TOPKLEAN EL 7 is an hydrocarbon-based cleaner for electronics. Due to its high flash point, TOPKLEAN EL7 can be used in printers to wet the paper rolls undercleaning stencils.

TOPKLEAN EL7 is qualified in MPM printers.

FEATURES

TOPKLEAN EL 7 is a light coloured, odourless liquid.

▪ Aspect	Clear
▪ Bulk density @ 15°C (kg/m ³)	761
▪ Flash point (°C)	60
▪ Distillation interval (°C)	187 - 212
▪ Viscosity @ 25°C (mm ² /s)	1.9
▪ Surface tension @ 20°C (mN/m)	23.5
▪ Relative evaporation speed (nBuAC = 1)	0.09
▪ Dielectric rigidity (kV/cm)	200
▪ Solubility in water	Not soluble
▪ Lower explosivity limit in air (% v/v)	0.57 (40 g/m ³)
▪ Upper explosivity limit in air (% v/v)	5.1 (360 g/m ³)
▪ Self-ignition temperature (°C)	375

BENEFITS

- ✦ TOPKLEAN EL 7 can also be used for cold manual cleaning of solderpaste on stencils and tools.
- ✦ Manual defluxing of PCB after rework.
- ✦ Compatible with all metals and their alloys as well as glass and ceramics.
- ✦ Can be recovered by vacuum distillation.



FRANCE

Sales Department
26, Avenue du Petit Parc
94683 VINCENNES Cedex
Tél. : (33) 1.43.98.75.00
Fax : (33) 1.43.98.21.51
Fax for order : (33) 1.49.83.92.17

ESPANA

PROMOSOL DIVISION IBERICA
Las Barcas 2 – 6°
Puerta 19-20
46002 Valencia
Tél. : (34) 96.353.51.93
Fax : (34) 96.353.51.92

BELGIUM

Av. Carton-de-Wiart, 79
P.O. Box 2
B 1090 Bruxelles
Tél. : (32) 2.425.00.20
Fax : (32) 2.425.96.62

NEDERLAND

Ekkersrijt, 1411
5692 AL SON
Tél. : (31) 499.47.47.05
Fax : (31) 499.47.48.28

PRODUCT DATA SHEET



CONDITIONS OF USE

TOPKLEAN EL 7 is used pure.

HANDLING PRECAUTIONS

TOPKLEAN EL 7 is chlorine- and halogenated solvent-free.
Comply with all relevant safety measures as concerns fire and explosion hazards.

REGULATION — ENVIRONMENT

TOPKLEAN EL 7 can be easily recycled, recovered or disposed of as used oil by specialised companies.

For more information, please consult our specialists.

PACKAGING — STORAGE

Available in 4 liters, 21 liters containers and 200 liters drums.

Keep product in closed conditioning.

Storage life : 18 months.

SAFETY & HEALTH

Please refer to MSDS.

The information given herein is offered as a possible helpful suggestion only. PROMOSOL assumes no liability whatsoever arising out of its use by others.

FPSGB 00016 TSI PRO 03 – 01.03/00



FRANCE

Sales Department
26, Avenue du Petit Parc
94683 VINCENNES Cedex
Tél. : (33) 1.43.98.75.00
Fax : (33) 1.43.98.21.51
Fax for order : (33) 1.49.83.92.17

ESPANA

PROMOSOL DIVISION IBERICA
Las Barcas 2 – 6°
Puerta 19-20
46002 Valencia
Tél. : (34) 96.353.51.93
Fax : (34) 96.353.51.92

BELGIUM

Av. Carton-de-Wiart, 79
P.O. Box 2
B 1090 Bruxelles
Tél. : (32) 2.425.00.20
Fax : (32) 2.425.96.62

NEDERLAND

Ekkersrijt, 1411
5692 AL SON
Tél. : (31) 499.47.47.05
Fax : (31) 499.47.48.28
